

Kemabind

Primer Bonding Coat

Description:

- **KEMABIND** is a bonding emulsion based on co-polymer of PVA for sealing cementitious surfaces.
- **KEMABIND** is also used as a primer or top coating for water-based paints as **KEMPLEKO** , **KEMAGRANO** , **KEMSTONE**.

Fields of Use:

- Priming cementitious surfaces as a sealing coat and to increase bond with subsequent water-based paints.
- Protecting **KEMPLEKO** , **KEMAGRANO** and **KEMSTONE** decorative plasters.

Advantages:

- Good adhesion to cementitious surfaces .
- Easy application .
- High coverage rate .
- Economic and decreasing paints cost.
- Resistant to the effects of ultraviolet rays.

Technical data :(at 25° C)

Density	1.02 ± 0.01 kg/l
Solid content	21 ± 1 %
Colour	transparent (when cured)
Min application temperature	4 ° C
Final curing time	8 hours
P.H	8.5 - 9.5
Theoretical rate of use	12 m ² / kg approx

Directions for Use:

- Surfaces should be cleaned free from dust, oils, grease ect..
- **KEMABIND** could be diluted with water in ratio 1 : 1 in case of application as a primer coat on cementitious surfaces or as a top coat for water based paints .
- **KEMABIND** could be applied by all paint application tools .

Storage:

- 12 months under suitable storage conditions.

Packages:

- 1 kg and 5kg.