

## Kema Putty

KEMA PUTTY is ready-to-use wall putty.

### Description:

- KEMA PUTTY is ready-to-use wall putty, based on vinyl acrylate polymer emulsion, especially selected fillers, binding materials and antibacterial agents.
- KEMA PUTTY is manufactured according to the technical specifications of our factories no. CMBI 7040.

### Uses:

- It is used for plastering and smoothing walls on ordinary and cement facing, interior and exterior concrete surfaces prior to application of all types of paints and sticking wallpapers.
- It can be used for filling all holes, fissures and hairline cracks without producing any cracks which often happens in case of using ordinary putty.

### Technical Characteristics: (at 25 ° C):

Density (kg/liter):	1.75 ± 0.05 kg / lt.
Viscosity:	130 ± 10 poise
pH:	7.5 – 8.5
Solid Content:	80 % ± 1 %
Consumption Rate:	0.5 kg / m <sup>2</sup> (The number of putty coats depends on the type of the surface)

### How to Use:

- Surfaces on which the putty will be applied should be dry and clean from oils, grease, dust, and any other contaminations.
- In Case of smooth surfaces, apply one coat of KEMA PUTTY using a normal putty knife. Apply two or more coats in case of coarse surfaces.
- Each coat must be dried and sanded down before applying the next coat.

**Storage:** 12 months under proper storing conditions.

**Packs:** 1 kg, 5 kg, 18 kg, 30 kg, 1 kg bag, 16 kg bag.