

### KEMATONE DELUXE PUTTY

**KEMATONE DELUXE PUTTY** is ready-to-use wall putty

#### Description:

- KEMATONE DELUXE PUTTY** is ready-to-use wall putty, based on vinyl acrylate polymer emulsion, especially selected fillers, binding materials and antibacterial agents.
- KEMATONE DELUXE PUTTY** is manufactured according to the technical specifications of our factories no. CMBI 7040.

#### Fields of Use:

- KEMATONE DELUXE PUTTY** is used for plastering and smoothing walls on ordinary and cementitious frosting, interior and exterior concrete surfaces prior to application of all types of paints and sticking wallpapers.
- KEMATONE DELUXE PUTTY** can be used for filling all holes, fissures and hairline cracks without producing any cracks which often happens in case of using ordinary putty

#### Technical Characteristics :( at 25° C)

Colour	White
Density ( kg / lt.)	1.75 ± 0.05
Soled Content:	68 ± 1%
Viscosity:	3000 ±1 50
PH:	8.5 - 9.5
Consumption Rate	0.25 – 0.5 kg / m <sup>2</sup>

#### Directions for Use:

- .Surfaces on which the putty will be applied should be dry and clean from oils, grease, dust, and any other contaminations.
- .In Case of smooth surfaces, apply one coat of **KEMATONE DELUXE PUTTY** using a normal putty knife. .Apply two or more coats in case of coarse surfaces..
- Each coat must be dried and sanded down before applying the next coat.
- Clean tools after use by water .

#### Storage/Shelf life

12 months in proper storing conditions.

#### Packages:

4 kg, 14 kg.