

## Rolltone 50

ROLLTONE 50 is high quality matt latex paint in compliance with the Egyptian Standard Specifications No. 1539 of 2008 (internal work).

### General Specifications:

- ROLLTONE 50 is bright weight matt emulsion paint, manufactured from vinyl acetate co-polymer resins, titanium dioxide and highly-smooth filling materials.

### Uses:

- ROLLTONE 50 is used for new and old, cement and gypsum surfaces.

### Technical Characteristics: (at 25 ° C):

Color:	White
Density:	1.6 ± 0.05 kg/L
Initial Drying Time:	20 - 30 minutes
Final Drying Time:	60 minutes
Dilution:	Diluted according to need with pure water
Consumption Rate:	4 - 5 m <sup>2</sup> / kg

### How to Use:

- Surfaces should be cleaned well from dust, oils, grease or any other contaminations.
- Cavities should be filled and surfaces must be smoothed. One or more coats of HANZA SEAL Sealer diluted with water can be painted.
- Paint one or more coats of ROLLTONE 50 according to the surface permeability.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

**Storage:** For one year under proper storing conditions.

**Packs:** 4 kg, 14 kg.



---

Headquarters: 319 – 43 Al Haram St. – Giza  
Tel.: 35854118 – 35854084 – 35853917 Fax: 35859858  
Email: [cmb@cmbegypt.com](mailto:cmb@cmbegypt.com)  
[www.cmb.eg](http://www.cmb.eg)

**16172** خدمة العملاء  
Customer Service