

Kema coat 400

Description & Fields of Use:

Emulsion acrylic washable paint used for interior purposes on old or new cement walls or walls, or a final face for ceilings, made of Aqueous Acrylic Copolymer, titanium dioxide, and super-soft materials, produced according to the Egyptian Standard No. 1539 of 2008.

Advantages:

- In door paint for concrete, render, brick and stone surfaces.
- High coverage rates.
- Washable with water.
- Easy to be coloured by plastic colorants.

Technical Characteristics: (at 25 ° C):

Colour:	White , Can be coloured upon request
Viscosity:	135 – 140
PH:	8.5 – 9
Density:	1.6 ± 0.02 gm/cm ³
	Solid Content by Weight : 69.3 % ± 2
	Solid Content by Volume : 50.7 % ± 2
Spreading:	5 – 6 Kg/m ² (For 50 – 60 µ thickness)

How to Use:

- Surfaces are thoroughly cleaned of dust, and free of oil or grease, and any materials stuck to it.
- Apply one Coat of sealer (Kema Coat 100) diluted by water 1:1.
- Fill the gaps, and adjust the surfaces by using one or more faces of the wall putty.
- Apply one or more layers of Kema Coat 400 depending on the degree of surface permeability.

Storage / Shelf life: Two Years under Suitable Weather Conditions, in it's original closed containers.

Packaging: Gallon 4 Kg, Pail 14 Kg.