

Addicon F

ADDICON F is a multi-purpose, high-quality, phosphoric acrylic paint.

General Specifications:

- ADDICON F is an acrylic-based compound, sprayed on different surfaces to strengthen and protect them against all external conditions.

Fields of Use:

- ADDICON F is used on concrete, gypsum, brick, asbestos, pottery, wood and iron surfaces.
- ADDICON is used in painted, fences, flower boxes, traffic marks, advertising boards, etc.

Technical Characteristics: (at 25° C)

Color:	White and other colors
Solid Content:	48 %
Density (kg/liter):	1.06
Surface Drying Time:	10 – 15 minutes
Hard Drying Time:	4 – 5 hours
Next Coat Painting Time:	6 hours
Minimum Thickness of Dry Coat:	40 micron
Temperature Resistance:	65 ± 5° C
Consumption Rate:	5 m ² / kg per coat

Method of Application:

- Concrete, gypsum, brick, asbestos, pottery, wood and metal surfaces should be cleaned well from dust, grease, and any other contaminations.
- In case on iron surfaces, remove rust and clean them well.
- Apply a primer coat of ADDICON (white color).
- Apply one or two coats of ADDICON Phosphoric with the required color after complete drying of the primer coat.
- Apply a final coat of ADDICON Transparent after complete drying of the previous coat.
- In case of working directly on clean surfaces, apply two or three coats of ADDICON F Phosphoric till complete covering with the required color, and then apply a finish coat of ADDICON Transparent as indicated above.
- Apply ADDICON with a soft brush or spraying. In case of spraying, dilute it with KIM SOLVE 6.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: For 3 years under proper storing conditions.

Packs: 0.5 kg, 1 kg, 3.75 kg, 13 kg.