

Kema Coat 700

High quality fine matt plastic paint for interiors

Description & Specification:

Kemacoat 700 is based on styrene-acrylic resin emulsions .
Complies with ES 1539 .

Fields Of Application:

- Interior finish coating of surfaces like concrete, masonry, asbestos, stone, plaster etc.
- Suitable for schools, Kindergartens, hospitals, satellite towns, office buildings, hotels etc.

Advantages:

- Is durable.
- Is very resistant to ageing, yellowing and alkalis.
- Is washable and has good abrasion resistance.
- Adheres well and can be applied on all smooth and rough, dry or moist surfaces.
- White and easy to colour if required.
- High flexibility and complies with ES (bending test).

Technical Characteristics: (at 25 ° C):

Colour:	White , our Catalog Colours
Density:	1.5 ± 0.05 kg/L
Viscosity ASTM D 562:	120 KU (Kerbs units)
PH:	8 – 9
Rate of use:	7 – 8 m ² / Liter / one coat

Directions for Use:

- The surfaces to be painted should be free of dust, Oil residues etc.
- Stir **Kemacoat 700** well before use.
- Porous surfaces should be primed with a sealer coat of **Kemacoat 100** diluted with water in the ratio 1:1.
- Cavities should be filled and Surfaces must be smoothed by using **Kemacoat 200**.
- Apply an undercoat of **Kemacoat 400** or **Kemacoat 700** diluted with water 10% maximum.
- Apply one or two coats of **Kemacoat 700** by brush, Roller or sprayer, to facilitate application **Kemacoat 700** can be diluted 5-10 % with water.
- All tools should be cleaned with water after use.

Storage / Shelf life: 2 years (in closed containers) under suitable storage conditions.

Packaging: 2.5 liter , 8.5 liter.