

## Kematone Matt

KEMATONE MATT is a high quality latex paint for interior and exterior use.

### General Specifications:

- KEMATONE MATT is a bright white matt latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.
- KEMATONE MATT complies with Egyptian Standard Specifications 1539.

### Uses:

- KEMATONE MATT is a matt paint for cement plastering, concrete, masonry, asbestos, wood and other surfaces.
- KEMATONE MATT can be applied on gypsum surfaces, after first applying a primer coat of ADDIBOND 65 diluted with water (ratio 1:3).

### Technical Characteristics: (at 25 ° C):

Color:	White & Colored
Density (kg/l.):	1.34 ± 0.02
Viscosity:	19.5 ± 1 poise
Consumption Rate:	6 – 8 m <sup>2</sup> / kg / coat

### How to Use:

- Surfaces should be cleaned well from dust, oil, etc.
- Porous surfaces should be primed with a sealer coat of KEMABIND diluted with water (ratio 1:2). Cavities should be filled and surfaces must be smoothed using one or more coats of KEMATONE FINE PUTTY. Then apply an undercoat of KEMACOAT 400.
- Stir KEMATONE MATT well before use.
- Apply one or two coats of KEMATONE MATT according to surface condition using a brush, roller or spray gun.
- In case of spraying, dilute KEMATONE MATT with 5 - 10 % water for ease of application.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

**Storage:** 12 months under proper storing conditions.

**Packs:** 1 kg, 4 kg, 9 liter.