

Kematone

KEMATONE is a high-quality semi-gloss latex paint for interior and exterior use.

General Specifications:

- It is a bright white semi-gloss latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.
- Complies with Egyptian Standard Specifications 1539.

Uses:

- Semi-gloss paint for cement plastering, concrete, masonry, asbestos, wood and other surfaces.
- It can be applied on gypsum surfaces, after first applying a primer coat of ADDIBOND 65 diluted with water (ratio 1:3).

Technical Characteristics: (at 25 ° C):

Color:	White & Colored
Density (kg/l.):	1.26 ± 0.02
Viscosity:	14 ± 1 poise
Consumption Rate:	8 – 10 m ² / kg / coat

How to Use:

- Surfaces should be cleaned well from dust, oils, etc.
- Porous surfaces should be primed with a sealer coat of KEMABIND diluted with water (ratio 1:1).
- Cavities should be filled and surfaces must be smoothed using one or more coats of KEMATONE Fine PUTTY.
- Apply an undercoat of KEMACOAT 400.
- Stir KEMATONE well before use.
- Apply one or more coats of KEMATONE according to surface condition using a brush, roller or spray gun. In case of spraying, dilute KEMATONE with 5 - 10 % water for ease of application.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months under proper storing conditions.

Packs: 1 kg, 4 kg, 25 liter, 9 liter.