

## Kingtone

High-quality bright gloss latex paint for interior and exterior.

### General Specifications:

- **Kingtone** is a high-quality bright white latex gloss paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide and auxiliary agents.
- Complies with ES 1539.

### Fields of Application:

- Gloss paint for cement plastering, concrete, masonry asbestos and wood surfaces.
- Can be applied on gypsum surfaces, after first applying a primer coat of **ADDIBOND** diluted with water in the ratio 1 : 2.

### Advantages:

- High coverage power with low consumption rate..
- Can be used for both exterior and interior applications.
- Resists the effects of atmospheric conditions, variations, ultraviolet rays and moisture.
- Bright white and can be tinted if required.
- Can be washed with water.
- High resistance to friction and abrasion.
- Fast drying, and durable.
- High flexibility and complies ESS (bending test).

### Technical Data: (at 25° C):

Color:	White
Density	1.22 ± 0.02 kg/liter
Solid Content:	49%
Viscosity	20 – 25 pois
PH – value	7.5 – 8.5
Elasticity elongation at break	1100 %
Washing and wet friction resistance	Confirms to ES.1539 for external paints
Alkali resistance	Resistant
Glossy	60 at 60° on minigloss model N 151 apparatus
Rate of use (theoretical)	8 – 10 m <sup>2</sup> / Kg / Coat

## Directions for Use:

- Stir **KINGTONE** well before use.
- Surfaces should be cleaned the well from dust, oils, etc.
- Porous surfaces should be primed with a coat of **KEMABIND** or **Hanza Seal**.
- Cavities should be filled and surfaces must be smoothed using one or more coats of “**KEMATONE DELUXE PUTTY**”, and then apply an undercoat of **KEMACOAT 400** and leave to dry.
- Apply one or more coats of **KINGTONE** using a brush or spray gun. In case of spraying, dilute **KINGTONE** with 5 - 10 % water for ease of application.

**Storage / Shelf life:** 12 months under proper storing conditions.

**Packaging:** 1 kg, 4 kg, 8.5 liter.