

Zenatone 700

High quality plastic matt paint for exteriors and interiors, Complies with ESS 1539

Description & Fields of Use:

Zenatone 700 is based on vinyl-acrylic emulsions.

Fields Of Application:

- Interior & Exterior coating of surfaces like concrete, masonry, asbestos, stone, plaster etc.
- Suitable for schools, Kindergartens, hospitals, satellite towns, office buildings, hotels etc.

Advantages:

- Is durable.
- Is very resistant to ageing, yellowing and alkalis.
- Is washable and has good abrasion resistance.
- Adheres well and can be applied on all smooth and rough, dry or moist surfaces.
- White and easy to colour if required.
- High flexibility and complies with ESS (bending test).

Technical Characteristics: (at 25 ° C):

Colour:	White , our Catalog Colours
Density:	1.5 ± 0.05 kg/L
Viscosity:	20 – 30 pois
PH:	8 – 9
Rate of use:	7 – 8 m ² / Liter / one coat

Directions for Use:

- The surfaces to be painted should be free of dust, Oil residues etc.
- Stir **Zenatone 700** well before use.
- Porous surfaces should be primed with a sealer coat of **KEMABIND** diluted with water in the ratio 1:1.
- Cavities should be filled and Surfaces must be smoothed the using wall putty **KEMAPUTTY**.
- Apply an undercoat of **Rolltone 50**.
- Apply one or two coats of **Zenatone 700** by brush, Roller or sprayer, to facilitate application **Zenatone 700** can be diluted 5-10 %.
- All tools should be cleaned with water after use.

Storage / Shelf life: 12 month (in closed containers) under suitable storage conditions.

Packaging: 2.5 liter , 9 liter. For White
0.9 liter , 3.3 liter , 9 liter. For Coloured