

Kema Clear

KEMA CLEAR is clear priming paint for interior and exterior surfaces.

Product Description:

KEMA CLEAR is a binding emulsion based on PVA (Polyvinyl Acetate) for sealing cement surfaces. It is used as a primer before applying water-based paints and for other purposes as protective top coating on water-based emulsion paints such as KEMPLEKO, KEMAGRANO and KEMSTONE.

Uses:

- KEMA CLEAR is primer for water-based paints to the strength of adhesion on cement surfaces of plastering or concrete.
- KEMA CLEAR is protective finish on KEMPLEKO, KEMAGRANO and KEMSTONE for weather protection.
- KEMA CLEAR facilitate operation, when necessary, for some materials such as KEMATONE Fine Putty, KEMACOAT, KEMPLEKO, KEMSTONE and KEMAGRANO.

Technical Characteristics: (at 25 ° C):

Density:	1.02 ± 0.02
Solid Content (by Weight):	21 ± 1 %
Color:	Transparent
Complete Drying Time:	8 hours
Theoretical Consumption Rate:	12 m ² / kg approx.

How to Use:

- Surfaces should be cleaned free from dust, oils, and grease.
- Dilute KEMA CLEAR with water in ratio 1:1. Apply KEMA CLEAR with brush, roller or spray gun as a primer coat on cement surfaces or as a sealer coat for protection and filling pores on water-based emulsion paints,.

Storage: 12 months in closed packs.

Packs: 4 kg