

Marmix S40 (Matt)

MARMIX S40 (MATT) is matt synthetic paint (white and colors).

General Specifications:

- MARMIX S40 (MATT) is a matt synthetic paint, based on alkyd and multiple high-quality additives.
- MARMIX S40 (MATT) is bright white and highly-resistant to yellowing (for the white color).
- MARMIX S40 (MATT) has a high coverage and withstands different weathering conditions.

Fields of Use:

- MARMIX S40 (MATT) is used to obtain matt finishes on wooden, metal and cement surfaces after preparing them with a suitable primer.

Application Method:

- Surfaces should be cleaned well from dust, oils, grease or any other contaminations.
- Smoothen surfaces with putty and then a suitable undercoat such as diluted MARMIX S40 (MATT), and finish with at least two coats of MARMIX S40 (MATT).
- Dilute MARMIX S40 (MATT) with mineral oil or turpentine or Kemsolve7 to obtain the suitable consistency.
- Paint with a brush, roller or spraying gun.

Technical characteristic: (at 25°C and humidity of 50%)

Color	White and colored
Solid Content	75% by (weight)
Initial drying	1 hour
Final drying	3-4 hours
Solvent	Mineral oil or turpentine or kemsolve 7

Spreading Rate: 6 – 8 m² / liter (Actual coverage rate depends on various factors such as color, the surface condition, and paint coat thickness,

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage and shelf/life: For 2 years from the date of production, provided that the pack is closed and stored away from direct sun rays.

Packs: 0.7 liter, 2.15 liter, 4.15 lite.