

Cementone

CEMENTONE is white or colored cement paint used in interiors, exteriors and facades.

General Description:

- CEMENTONE is a colored powder for painting facades and consists of cement, graded fillers and polymer additives

Fields of Use:

- CEMENTONE is used to paint walls on normal plastered and cement surfaces.
- CEMENTONE is used to apply protective cement coats on facades in coastal buildings.
- CEMENTONE can be used to fill all gapes, cracks, and fissures without deforming the paint.
- CEMENTONE is used to paint residential units from housing projects, low-income units to villas.

Technical Characteristics: (at 25° C)

Color:	White - Colored
Density before Mixing:	1.2 ± 0.05
Addition Rate:	20 kg of CEMENTONE is mixed with about 14 - 16 liters of water + one pack of CEMENTONE (B) Liquid, if necessary.
Spreading Rate:	2 – 3 m ² / kg / Coat (depending on the condition of the surface)

Method of Application:

- The surface should be cleaned from any contaminations and oils, and then wetted with water.
- Apply to coats of PERFECT Cement Putty to smoothen surface.
- Add about 8 liters of water in a mixing container, and then add the contents of CEMENTONE Powder gradually with mechanical mixing using a mixer (or drill), adding an additional amount until it smoothen and reaches the required consistency, taking into account stirring at intervals to ensure consistency.
- Apply the product with a brush or roller. It can be diluted with little water in case of spraying or hot weather/
- Apply the second coat if necessary after drying (not less than 6 hours) of the first coat. It's recommended to wet the surface with water before applying the next coat.
- To increase the hardness of the surfaces, especially in coastal areas, it's recommended to add a pack of CEMENTONE (B) to each bag.
- Used tools should be cleaned by being directly stirred with water after use.

Storage / Shelf life: For one year under suitable and dry storing conditions.

Packs: Bags of 20 kg.