

## Dary LIFE

Ready-made mortar, white and colored, smooth and coarse for building facades and decoration works.

### Product Description:

- Dary Life is a cement based pre-mixed decorative renders, chemically developed to use as a final finishing layer for building facades, supplied in a powder form which only require addition of water prior usage in site.

### Composition:

- Consists of Portland cement, selected graded fillers, special binders, high quality pigments and special chemical additives to enhance workability, adhesion and weather resistance.

### Advantages:

- Breathable.
- Available in attractive 43 colors, special colors upon request.
- Weather resistant.
- Controlled raw materials according to highest quality standards.
- Ease of use, only add water to have a homogenous mix.
- High coverage rates.
- Various textures and aesthetic shapes with different degrees of roughness

And thicknesses according to the following table:

PROPERTY	Dary Life 201	Dary Life 201M	Dary Life 202	Dary Life 402	Dary Life 203
Texture	Smooth	Between Smooth & Medium	Medium	Between Medium & Rough	Rough
Thickness	0.5 – 1 mm	1 – 1.5 mm	1.5 – 2 mm	2 – 2.5 mm	2.5 – 3 mm

### Technical Characteristics: (at 25°C)

PROPERTY	Dary Life 201	Dary Life 201M	Dary Life 202	Dary Life 402	Dary Life 203
Density kg/l	1.3	1.31	1.32	1.35	1.38
Mixing water rate L / sack 40 kg	8.8 – 10.8	8.8- 10.8	8.8- 10.8	8.8 – 10.8	8.8 – 10.8
Coverage rate m <sup>2</sup> / sack 40 kg	16 - 18	15 - 17	13.5-15.5	12 - 14	10 - 12

To Be Continued ...

## Dary LIFE 201, 202, 203 (Cont.)

### Technical Data: (at 25°C)

- Compressive strength:	240 – 290	Kg/m <sup>2</sup>
- Bond strength with concrete:	1.2	MPa
- Hardness:	15.6	MPa
- Alkali resistance:	Na OH 10%	Comply
- weather resistance:	RH 90% & 60°C	Comply
- UV resistance:		Comply

### Directions for Use:

- Surfaces should be cleaned from dust, oils and grease.
- Surfaces should be sprayed with water before application.
- Add 8 – 10 liters of water to each sack 40 kg of Dary Life and stir well for 5 minute.
- Spread the material on the surface with a trowel or spraying machines in the required thickness.
- Finish the surface with plastic float to get the required effect, taking into account not to add additional water to the mix
- Protect surfaces exposed to dust and water splatters, like the lower part of façade with Kemtekt.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

### Safety Precautions:

- Wear gloves, overall, and glasses during handling and application.
- In case of skin contact, wash exposed area with plenty of water. In case of eye contact, consult a physician.

**Storage:** For 12 months from the date of production in closed packs in a dry store away from humidity.

**Packs:** 40 kg ± 2% bags.