

Kema Graviato

High quality acrylic exterior and interior textured plaster.

Description:

- This is an acrylic copolymers exterior & interior, architectural texture coating.
- It is uniquely formulated with exceptional extenders, pigments and special additives.
- Available in three types fine, medium (with 2mm. stones) and coarse (with 3 mm. stones) .

Fields of Use:

- On fair faced concrete and plastered surfaces.
- On wood surfaces and MARMOX boards.

Advantages:

- Provide unique texture of its own with different degree of roughness.
- Texture coating with outstanding exterior durability.
- Eco-friendly product since it is completely water-based.

Technical Data :(25°C)

Color:	White & Colored	
Density:	2.1 ± 0.05	Kg/L
Viscosity:	475000 ± 5000	Centipoise
Solid Content:	86.5 ± 1	%
Initial Dry Time:	30 - 60	Minutes
Final Dry Time:	24	Hours
Rate Of Use		
For Fine Type:	1.25 - 1.5	Kg/m ²
For Medium Type:	2.5 - 3.25	Kg/m ²
For Coarse Type:	4 - 4.5	Kg/m ²

Directions for Use:

- Work is done on a clean surface free of oils, grease and dust.
- Primer paint with KEMACOAT 100 or Hanza Seal in a color similar to the color of Kema GRAVIATO.
- Spread the required layer of Kema GRAVIATO using a trowel at the spreading rate indicated in the technical properties.
- Excess parts are removed using a trowel.
- Leave the surface for about five minutes and then go over it again using the plastic trowel to obtain the desired shape.
- The product can be diluted with water, if necessary, up to a maximum of 5%.
- Used tools should be cleaned with water directly after use.

Safety Precautions:

- Application should be carried out in a ventilated place.
- Gloves, protective clothing and eye goggles should be worn during application.
- Skin contaminations should be cleaned with a plenty of water.
- If the material is splashed into the eyes, these should immediately washed with water and then report to an eye specialist.
- Do not eat or smoke during application.

Storage/Shelf life:

- For a period of 12 months in the original closed packaging under appropriate storage conditions away from direct sunlight and heat.
- Packages:
- Bags 20 Kg.

DISCLAIMER: The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control, we can only guarantee the quality of the product itself. We also reserve the right to change the given data without notice minor product variations may be implemented in order to comply with local requirements.