

Kemagrano

KEMAGRANO is decorative granulated plaster for luxurious interiors and facades.

Product Description:

- A tough elastic plaster for interior and exterior surfaces.
- Made of acrylic resins and carefully selected quartz granules and natural fibers with different types, colors and gradient.
- KEMAGRANO is produced in accordance with the technical specifications of the company CMBI 7020.

Fields of Use:

- Exterior and interior finish for different surfaces such as concrete, masonry, gypsum boards, asbestos, plaster, wood....
- Suitable for offices, hotels, hospitals, schools, public and private buildings, shops and dwelling buildings.

Technical Characteristics: (at 25 ° C):

Color:	One Color or different overlapping colors
Density (kg / liter):	1.7 ± 0.05
Consumption Rate:	3 – 5 kg / m ² for film thicknesses of 2 - 3 mm

Application Method:

- KEMAGRANO is ready to be applied by normal plastering tools.
- It can be used directly on all sound and dry surfaces.
- Weak or porous plastering undercoat must be treated with a primer coat of ADDIBOND diluted by 1 : 5 with water or KIMABIND before applying the coat of KIMAGRANO.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: For 9 months under proper storing conditions.

Packs: 1 kg, 5 kg, 18 kg.