

Kempleko

KEMPLEKO is decorative paint (Fine, Medium and Coarse) for interior and exterior walls.

General Specifications:

- KEMPLEKO 700 (fine) is a decorative white and colored paint for making multi shapes, based on modified vinyl acrylic co-polymer and contains especial fine fillers and pigments.
- KEMPLEKO 800 (medium) is a decorative white and colored final paint, based on modified vinyl acrylic co-polymer and contains especial medium-coarse fillers and pigments.
- KEMPLEKO 900 (coarse) is a decorative white and colored final paint, based on modified vinyl acrylic co-polymer and contains especial coarse fillers and pigments.
- KEMPLEKO is manufactured in compliance with the technical specification of CMBI 7010.

Fields of Use:

- Exterior and interior finish for different surfaces like concrete, buildings, gypsum boards, asbestos, plastering, wood...
- Suitable for offices, hotels, hospitals, schools, public and private buildings, shops, and dwelling buildings.

Technical Characteristics: (at 25 ° C):

	Type		
	Fine 700	Medium 800	Coarse 900
Color	White or Colored	White or Colored	White or Colored
Density (kg / liter)	1.80 ± 0.05	1.95 ± 0.05	1.95 ± 0.05
Solid Content by Weight %	82 % ± 5 %	86 % ± 5 %	85 % ± 5 %
Consumption Rate (kg / m ²)	1 – 2	2 – 3	2.5 – 3.5

How to Use:

- Surfaces should be dry, clean and free of oil, grease, dust or any other contaminations.
- Weak and absorbent surfaces should be treated with KEMABIND primer diluted with water by 1 : 1.
- Stir the material well inside a wide plastic container.

KEMPLEKO 700

- Spread KEMPLEKO 700 by a trowel, spraying machine or roller (cotton, wool, sponge).

Kempleko (Cont.)

KEMPLEKO 800

- Spread KEMPLEKO 800 by a steel trowel or spraying machine after suitable dilution and good mixing.

KEMPLEKO 900

- Spread KEMPLEKO 900 by a steel trowel at a thickness equal to the granules in the material.
- After 5 minutes, pass plastic trowel in a vertical or circular manner according to the required decorative shape.
- For exterior facades in coastal regions, apply a final coat of KEMABIND on the KEMPLEKO coat.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: For 12 months under proper storing conditions.

Packs: 1 kg, 5 kg, 16 kg.