

## Rolplast

ROLPLAST is ready-to-use, multi-colored, decorative paint.

### Field of Use:

- Internal paints.

### Advantages:

- Multi-color – matt paint – mild odor.

### Technical Characteristics:

Pigments:	Colored scales
Density:	1.24 ± 0.01 kg / liter
Drying Time:	6 – 10 hour
Final Harding Time:	24 hours (at 20° C and 65% relative humidity)

### Application Method:

- Surfaces must be dry and free of dust and grease. Any defects must be treated before work.
- Apply a primer coat with a paint that contains quartz granules tinted with a color matching the color of ROLPLAST.
- Apply ROLPLAST with a roller or spraying.

### Consumption Rates:

- By the roller:
  - o First Coat: about 400 gm. / m<sup>2</sup>.
  - o Second Coat: about 200 gm. / m<sup>2</sup>.
  - o Complete Rate: 600 gm. / m<sup>2</sup>.
- By Spraying: 800 gm. / m<sup>2</sup>.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

**Storage:** At least 18 months from the date of production.

**Packs:** For spraying: packs of 1 kg and 4 kg.  
For the roller: packs of 2 kg and 8 kg.