

## Marmitone

### Description:

- MARMITONE is water-based putty, consisting of special materials to give marble effect and other decorative effects such as wood, wallpaper and others.
- MARMITONE gives a final appearance that combines luxury and elegance and give multiples option for interior decoration.
- MARMITONE complies with the internal specifications of our factories CMBI 7090.

### Fields of Use:

- MARMITONE is designed especially for internal surfaces of cement plaster, concrete, gypsum boards, wood and others. It's recommended to be used for interior finishes of luxurious buildings such as hotels, restaurants, villas, mosques, museums, art galleries as well as halls, entrances of different buildings and others.

### Technical Characteristics:

Solid Content Ratio (% in weight):	80 ± 1
Theoretical Coverage Rate:	0.7 – 1 varies depending on thickness (based on the application method)

### Application Method:

- Application Tools: Putty Knife or trowel (provided that it's stainless steel)
- Diluter: Water

### Surface Preparation for Painting:

- Surface must be hard, dry, clean and free from dust and oils. Residues of sanding must be removed, and the surface must be cleaned upon application. All disconnected parts must be removed using a thick brush, and all defects in the surface must be filled with KIMA PUTTY after painting the surface with KIMABIND.
- Paint the surface with two coats of KIMACOAT 400. It's preferable to be tinted with the closest color to that of MARMITONE. Apply it using a putty knife in a small piecemeal manner, and then sand it to get a smooth and glossy surface. You can get the glossy effect by touching the product with the trowel whether it's soft or dry.
- Repeat the previous process three or four times at least to get a smooth and marble-effect surface, increase gloss, prevent water absorption, and increase washability.
- Apply one coat of special wax by a cotton piece, and then polish the surface.

To Be Continued...

### Marmitone (Cont.)

- To obtain the wood effect, spread MARMITONE with the required color, and then use the wood graining tool to obtain the wood appearance in the required effect. Apply a finish coat with another color by the putty knife.
- To obtain other decorative effects, follow the previous steps, but use the stamping roller with the desired effects.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

**Storage:** 12 from the date of production. Storing must be in accordance with the local laws. Store it in a cool place with good ventilation away from heat and direct sunlight. Packs must be kept tightly closed. Handle with care and stir well.

**Packs:** 1 kg, 4 kg.