Paints, Plasters & Putties



Swahelly

Swahelly is a water-based paint, manufactured from high-quality acrylic resins and coloring pigments which give attractive pearl effect and a touch of luxury and elegance.

Advantages:

- Attractive pearl colors.
- Good washing resistance.
- Distinctive decorative effects.

Fields of Use:

- It can be used on cement, wood, gypsum and metal surfaces.

Technical Characteristics:

Colors: Available in all colors according to CMB Color Card

Surface Drying: 1.5 - 2 hours Complete Drying: 72 hours

Consumption Rate: $8 - 10 \text{ m}^2 / \text{liter}$

Used Tools: Roll – Trowel – Stamping sponge

Application Method:

- The surface should be clean, completely flat and free from dust and grease.
- Apply a primer coat of KEMABIND WATER SEALER.
- Smoothen the surface using KEMATONE FINE PUTTY.
- Sand the putty well.
- Apply one coat of KEMACOAT 700 in case of stamping and one coat of KEMATONE in case of using the trowel.
- Apply the first coat of Swahelly in the required color, leave it to dry for an hour, apply a final coat, and then use the trowel in circular way to give attractive decorative effects.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months from the production date under proper storing conditions.

Packs: 0.45 liter, 0.9 liter.

Headquarters: 319 – 43 Al Haram St. – Giza Tel.: 35854118 – 35854084 – 35853917 Fax: 35859858

Email: cmb@cmbegypt.com www.cmb.eg

خدمة العملاء Customer Service