

Velvet

Velvet is a water-based paint, manufactured from high-quality acrylic resins and coloring pigments which give attractive pearl effect and a touch of luxury and elegance.

Advantages:

- Attractive pearl colors.
- Good washing resistance.
- Distinctive decorative effects.

Fields of Use:

- It can be used on cement, wood, gypsum and metal surfaces.

Technical Characteristics:

Colors:	Available in all colors according to CMB Color Card
Density:	1.09 gm/Cm ³
Surface Drying:	1.5 – 2 hours
Complete Drying:	72 hours
Solid Content:	42%
Consumption Rate:	6 – 8 m ² / Kg.
Used Tools:	Roll – Trowel – Stamping sponge, ...etc.

Application Method:

- The surface should be clean, completely flat and free from dust and grease.
- Apply a primer coat of KEMABIND WATER SEALER or Hanza Seal.
- Smoothen the surface using KEMATONE FINE PUTTY.
- Sand the putty well.
- Apply 2 coats of Kematone Matt or Zenatone with the same required colour.
- Apply the first coat of Velvet in the required color, leave it to dry for an hour to 1.5hours, apply a final coat, and then use the trowel in circular way to give attractive decorative effects.
- In the case of finishing using stamping sponge, the work is done as previously with diluting Velvet with fresh water to the required consistency for the stamping process.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months from the production date under proper storing conditions.

Packaging: 0.9 Kg, 2.7 Kg.