

Bio Kematone Matt

BIO KEMATONE MATT is Bactericidal and fungicidal matt latex paint in compliance with the Egyptian Standard Specifications 1539 of 1993.

Description:

- BIO KEMATONE MATT is a bright white matt latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.

Technical Characteristics: (at 25 ° C):

Density:	1.34 ± 0.02 kg/ltr.
Viscosity:	15 – 20 poise
pH	7.5 – 8.5
Consumption Rate:	6 – 8 m ² / kg

Application Method:

- Stir BIO KEMATONE MATT well before use.
- Surfaces should be cleaned well from dust, oil, etc.
- Cavities should be filled and surfaces must be smoothed using BIO KEMA PUTTY.
- Porous surfaces should be primed with a coat of BIO KEMABIND.
- Apply one or two coats of BIO KEMATONE MATT according to surface condition using a brush, roller or spray gun. In case of spraying, dilute BIO KEMATONE MATT with 5 - 10 % water for ease of application.
- Tools should be cleaned with water after use.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months in tightly-sealed packs under proper storing conditions.

Packs: 1 kg, 4 kg, 9 liter.