

Bio Kematone

BIO KEMATONE is bactericidal and fungicidal semi-gloss latex paint for interior and exterior use.

General Specifications:

- BIO KEMATONE is a bright white semi-gloss latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.

Technical Characteristics: (at 25 ° C)

Density:	1.29 ± 0.02 kg/liter
Viscosity:	15 – 20 poise
pH	7.5 – 8.5
Consumption Rate:	8 – 10 m ² / kg

Application Method:

- Stir BIO KEMATONE well before use.
- Surfaces should be cleaned well from dust, oil, etc.
- Cavities should be filled and surfaces must be smoothed using BIO KEMA PUTTY.
- Porous surfaces should be primed with a coat of BIO KEMABIND.
- Apply one or two coats of BIO KEMATONE according to surface condition using a brush, roller or spray gun.
- In case of using a brush or spraying, dilute BIO KEMATONE with 5 - 10 % water respectively.
- Tools should be cleaned with water after use.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months under proper storing conditions.

Packs: 1 kg, 4 kg, 9 liter.