

Alkyd Traffic Paint CMB

Special ready-to-apply paints, based on alkyd resin, for marking roads and traffic signs

Product Description:

- Ready-to-apply paints of one component, based on alkyd resin, pigments, and special filling materials, which have high resistance to weather conditions, chemicals and petroleum materials.
- Complies with E.S. 794 Type 2.

Fields of Use:

- Marking streets, roads, garages, car parks, playgrounds, and making prominent traffic signs.

Technical Characteristics: (at 25° C)

Solid Content:	No less than 65 % by weight
Density (kg/liter):	1.35 ± 0.02 for black, 1.65 ± 0.05 for white and yellow
Recommended Minimum W.F.T.	150 – 200 micron
Surface Drying Time:	Not more than an hour
Hard Drying Time:	Not more than 3 hours
Colors:	White – Yellow – Black
Abrasion Resistance (Taber Abraser):	No less than 1500 cycles
Consumption Rate:	250 gm. / m ² / kg per coat

Application Method:

- Floors should be cleaned well from oils, grease and dust. The final cleaning can be done by air compressor or sandblaster.
- Apply one or more coats according to the required specifications using a brush, roller or spray gun. The next coat is painted after 45 minutes from the first coat.
- Used tool should be cleaned with KIM SOLVE 22 C.

Storage: For 3 years under proper storing conditions.

Packs: 5 kg, 20 kg.