

## Kema Kurb

KEMA KURB is a special paint for curbstones and sidewalks.

### General Specifications:

- Ready-to-apply paints of one component, based on alkyd resin, pigments, and special filling materials, which have high resistance to weather conditions.

### Fields of Use:

- KEMACURB is used for curbstones and sidewalks in roads, garages, car parks, playgrounds, clubs, etc.

### Technical Characteristics: (at 25 ° C)

	White	Black
Gloss:	Semi-gloss	Semi-gloss
Solid Content:	70 ± 1%	65 ± 1%
Density (kg/cm <sup>3</sup> ):	1.39 ± 0.01	1.29 ± 0.01
Viscosity (Ford Cup No. 4):	110 – 130	110 – 130
Surface Drying Time (minute):	60	60
Hard Drying Time (Hour):	3	3
Minimum Thickness of Dry Coat (micron):	700	70
Consumption Rate (m <sup>2</sup> / kg / coat):	4 – 5	4 – 5

### Application Method:

- Surfaces should be cleaned well from dust, oils, grease, and loose particles, and then a coat of a suitable primer should be painted.
- Stir the pack well before use.
- Dilute KEMACURB by adding mineral oil or turpentine to obtain the suitable consistency for use as needed.
- KEMACURB can be painted by a roller, brush or spray gun.

**Storage:** For 3 years under proper storing conditions.

**Packs:** 5 kg, 20 kg.