

Traffic Paint CR

Special paints for marking roads and traffic signs.
In compliance with the Egyptian Standard Specification 794/1995 Types (1)

Description:

- Ready-to-apply paints of one component, based on chlorinated rubber, pigments, and special filling materials, which have high resistance to weather conditions, chemicals and petroleum materials.

Fields of Use:

- Marking streets, roads, garages, car parks, playgrounds, and making prominent traffic signs.

Technical Characteristics: (at 25° C)

Colors:	Black, White, Yellow and other colors
Gloss	Egg shell
Density (kg/liter):	1.42 ± 0.05
Solid Content:	Not less than 60 % by weight
Initial Drying Time:	10 – 15 minutes
Hard Drying Time:	45 – 60 minutes
Abrasion Resistance (Taber Abraser):	Not less than 1500 cycles
Thinner	KemSolve 6 (5 – 10 % for first coat if required)
Rate of use (Theoretical)	200 - 250 gm / m ² / coat

Application Method:

- Floors should be cleaned well from oils, grease and dust, by suitable tools or sand blasting The final cleaning can be done by compressed air.
- Apply one or more coats according to the required specifications using a brush, roller or spray gun.
- The next coat should be painted after 45 minutes from the first coat.
- Used tool should be cleaned with KEM SOLVE 1.

Storage / Shelf life: For two years under proper storing conditions.

Packaging: 4 kg, 16 kg.