

KEMLUX 999

High glossy synthetic enamel paint

Description:

- **KEMLUX 999** is a high glossy synthetic enamel paint based on alkyd resin.

Fields of Use:

- Can be applied on synthetic primer or undercoat, or on both.also, on wooden, metallic and plastered surfaces.

Advantages:

- Acquires an homogenous consistency by manual mixing.
- Easy to apply.
- High coverage because of the use of finely grounded and high quality pigments.
- After drying, it produces glossy elastic homogenous film, that is well adhered to the substrate and resists abrasion and scratching.

Technical Characteristics:

Colour:	White and coloured
Density:	1.19 ± 0.05 gm/cm ³ depend on colour
Solid content:	70 ± 3%
Viscosity FC/4:	120 - 150 second
Surface dry:	3 hours
Hard dry:	12 hours
Recoat time:	18 hours
Thinner:	KEMSOLVE 7
Rate of use:	1Kg. covers 8 - 10 m ² per each coat (depend of substrate)

Directions For Use:

- The surface of the substrate should be cleaned from oil, grease, dirt and loose particles.
- Mix well the contents of the can before use.
- The substrate should be primed and/or coated with a suitable undercoat (As **KEMLACQUER**) then left to dry and smoothed down with sand paper.
- Two coats of **KEMLUX 999** are recommended. Apply the second coat after the first coat has completely dried.
- Can be applied using brush, roller or spraying

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Safety Precautions:

- Application should be carried out in a well ventilated place.
- Gloves, protective clothing and eye specialist.
- Do not eat or smoke during use.

Storage:

- 3 year in closed containers under suitable conditions.

Packages:

- 0.7 L , 2 L , 3.65 L