

CMB ALUMINIUM PAINT

High Thermal Resistant Steel Coating

DESCRIPTION:

- CMB ALUMINIUM PAINT is a thermal aluminium paint for steel surfaces exposed to high temperatures .

FIELDS OF USE :

- Boilers, machine rooms, chimneys and all surfaces that are subjected to high temperature .

Advantages:

- Good resistance to high temperatures.
- High bonding strength to steel surfaces.
- Fast drying easy application.
- High resistance to friction and abrasion.
- Economic, high coverage rate.

TECHNICAL DATA:

Density	1.04kg/l
Solid content	50%
Viscosity (FC/4)	35-40 seconds
Heat resistance	180°C
Surface dry	60 minutes (at 25°C)
Hard dry	18hours(at 25°C)
Recoating time	18hours(at 25°C)
Tinner	KEMSOLVE 6
Rate of use (theorrtical)	10 m2 /kg/coal

DIRECTIONS FOR USE :

- The surface of steel should be well cleaned, dry, free from rust.
- Stir CMB ALUMINUM PAINT before use.
- CMB ALUMINUM PAINT could be applied by brush or spray .

Safety Precautions:

- Application should be carried out in well ventilated place.
- Gloves, protective clothing and eye goggles should be worn during application.
- Skin contaminations should be immediately cleaned with soap and plenty of water. Don't use solvent.
- If the material is splashed into the eyes, they should be immediately washed with water and then report to an eye specialist.
- Do not eat or smoke during application.

Storage / shelf life:

- 12 months under suitable storage conditions

PACKAGES

- 4 kg



Chemicals for Modern Building
Head Office: 319 El- Haram St., Giza.
Tel: +(202) 35853917 - 35854084 - 35854118 Fax: +(202) 35859858

Great Products