

KEMFAST

Protective Coloured Glossy Paint For Metallic Surfaces

DESCRIPTION :

- KEMFAST is a glossy paint based on high quality synthetic resins, for painting metallic surfaces exposed to severe conditions .

FIELD OF APPLICATION:

- Metallic surfaces of permanently exposed bodies to severe conditions during refilling and transporting as gas tanks, grease and oil barrels .
- Metallic surfaces exposed to different atmospheric conditions as trailers, tractors, wagons .etc .

ADVANTAGES:

- High resistance to different atmospheric conditions .
- High resistance to friction and abrasion .
- High bonding strength to steel surfaces .
- Fast drying and easy application .
- High temperature resistance .
- Equipment protection .

TECHNICAL DATA:

Density	1.1 - 1.2 gm/cm ³
Colour	Blue, red, (other colours upon request)
Touch dry	20 - 25 minutes. (at 25 °C)
Hard dry	24 hours (at 25 °C)
Full curing	3days(at25 °C)
Heat resistance	120 °C (ASTM D 2485)
Coverage rate	8 - 10 m ² / kg
DFT	30 - 40 micron
Viscosity	120-250sec(FC/4)at25°C
Bond strength	Conforms with DIN 53151
Bending strength	Conforms with DIN 53152
Thinner	KEMSOLVE 6
Tool Cleaner	KEMSOLVE 66

DIRECTIONS FOR USE:

- The surface should be cleaned from any impurities before KEMFAST application .
- KEMFAST could be applied by brush or spray .

STORAGE:

- 2 years under suitable storage conditions .

PACKAGES:

- 4 kg, 16 kg.