

## Zetolan S

Chemical release agent for concrete shuttering.

### Description:

- **ZETOLAN S** is a special formulated agent with chemical release properties, enabling easy stripping from concrete. it is far superior to traditional form oils.
- **ZETOLAN S** reacts with water in concrete to form a thin water repellent layer on the surface of the shuttering, thus enabling easy stripping from concrete and acts as a protection layer to steel and wooden shuttering.

### Fields of Use:

- Can be used with all types of mould and concrete shuttering.

### Advantages:

- Ensures stain free concrete and reduces the incidence of blow holes.
- Can be used for all types of moulds and concrete shuttering.
- Does not cause the loss of bond to paint, plaster or wallpaper.
- Minimizes the cleaning of the shuttering due to its anti-electrostatic effect, thus lengthens its life.
- It protects woods against water penetration and deterioration, and protects steel against corrosion.
- It is suitable for steam and high temperature curing systems.
- It saves time and money.

### Technical Data :( at 25° C)

Density	0.84 ± 0.01 kg/l
Flash point	Over 65°C.
Temperature stability	From -30°C to +100°C
Rate of use	40 – 50 m <sup>2</sup> /L on metal, fiberglass, or coated timber
(depending on used tool)	20-25 m <sup>2</sup> /L on timber

### Directions for Use:

- For new shuttering no preparation of the surface is required.
- For used shuttering, all traces of cement and previously used form oils must be removed.
- **ZETOLAN S** is applied by brush, roller, sprayer or sponge in the form of a uniform thin coating prior to concreting.
- On metal, glass-fiber or any other impervious surface, one coat of **ZETOLAN S** is sufficient. On new plain timber surfaces a further coat of **ZETOLAN S**, should be applied before placing concrete.

### Safety Precautions:

- Wear gloves and goggles.
- Skin and face contamination should be washed with water and soap.
- Accidental splashes to eyes must be rinsed with clean warm and then report to an specialist.
- Do not eat and smoke during use.

### Storage:

- 5years under suitable storage conditions.

### Packages:

- 20 litre and 200 litre.