

Verona Sealer Polyester 5000 Transparent

High-quality wood polyester sealer consisting three components.

Specifications:

- Verona Sealer Polyester transparent is a high-quality clear wood sealer, consisting three components.

Features:

- High filling of wood pores and ease of sanding.
- Flattening wood surfaces and preparing them for spraying with the appropriate finishing varnish.
- Enduring different weather conditions.

Uses:

- Used to prepare all woodworks such as furniture and kitchens.

How to use

- Prepare surfaces well before use. For the best results, use polyurethane sealer before polyester sealer.
- Mix Sealer with Cobalt Accelerator 5005 by 2% of the sealer.
- Dilute Verona Polyester Sealer by adding 20 – 30 % using polyurethane thinner to get the appropriate viscosity for use.
- Add Peroxide 5010 by 2% of the sealer directly before painting.
- Use a spray gun with a diameter of 2 – 2.5 mm.
- Spray within 15 – 20 minutes after mixing the sealer with the hardener.

Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 60 – 90 minutes.
- Hard Drying: 2 – 3 hours.
- Sanding: 17 – 18 hours.
- Consumption rate: 4 - 5 m² / kg per film thickness of 40 microns.

Public Safety and Health Guidelines:

- Avoid contact with skin and eyes.
- Wear a protective mask to avoid inhaling spray from painting.
- Close the container tightly after use.
- Keep out of the reach of the children.
- The product is flammable.

Storage: For one year from the date of production provided that the pack is kept closed and away from direct sunlight.

Packs: A set of 3 components 1 kg, 3 kg, 4 kg, 9 kg, 14 kg, 23 kg & 200 kg/baril.