

Verona Sealer Polyurethane 2:1 Clear

High-quality polyurethane sealer for wood and parquet, consisting of two components 2:1.

Specifications:

- Verona Sealer 2:1 Clear is a high-quality clear sealer for wood and primer for parquet and wood floors, consisting two components with polyurethane base and manufactured from high-quality resins.

Features:

- High filling of wood pores, flattening surfaces and preparing them for spraying with the appropriate finishing varnish.
- Enduring different weather conditions and abrasion-resistant.

How to use

- Prepare surfaces well before use.
- Mix Sealer with Hardener 1000 by 2:1 directly before painting.
- Dilute Verona Polyurethane Sealer 2:1 by adding 20 – 30 % using polyurethane thinner (Thinner S) to get the appropriate viscosity for use.
- Use a spray gun with a diameter of 1.4 – 1.6 mm.
- Spray within 4 – 5 hours after mixing the sealer with the hardener.

Sanding: Re-spraying can be done after sanding surface using sandpaper no. 320 after 2 – 3 hours.

Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 15 – 30 minutes.
- Hard Drying: 2 – 3 hours.
- Consumption rate: 9 - 11 m² / kg per film thickness of 40 microns.

Public Safety and Health Guidelines:

- Avoid contact with skin and eyes.
- Wear a protective mask to avoid inhaling spray from painting.
- Close the container tightly after use.
- Keep out of the reach of the children.
- The product is flammable.

Storage: For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

Packs: A set of 2 components 1.35 kg, 6 kg, 6.75 kg, 13.5 kg, 34.25 kg.