Wood Paints and Varnishes



Verona Polyurethane Glossy Varnish 2:1

High-quality, glossy wood polyurethane varnish 2:1 of two components.

Specifications:

- Verona Polyurethane Glossy Varnish 2:1 is a final, high-quality and glossy clear varnish for wood, consisting of two components, based on polyurethane.

Features:

- High gloss, clearness, strong adhesion, hardness and high residence to scratching and different weather condition.

How to use

- Prepare surfaces with suitable sealer, and sand it well.
- Mix Varnish with Hardener 3000 by 2:1 directly before painting.
- Dilute Verona Polyurethane Gloss Varnish 2:1 by adding 20 30 % using polyurethane thinner (Thinner S) to get the appropriate viscosity for use.
- Use a spray gun with a diameter of 1.4 1.6 mm at air pressure of 4-5 bar.
- Spray within 4 5 hours after mixing the varnish with the hardener.

Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 40 60 minutes.
- Hard Drying: 6 8 hours.
- Gloss at 60°: 90 95
- Consumption Rate: 9 11 m² / kg per film thickness of 40 microns.

Safety Warnings:

- Avoid contact with skin and eyes.
- Wear a protective mask to avoid inhaling spray from painting.
- Close the container tightly after use.
- Keep out of the reach of the children.
- The product is flammable.

Storage: For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

Packs: A set of two components 1.35 kg, 6.375 kg, 6.75 kg.

Headquarters: 319 – 43 Al Haram St. – Giza Tel.: 35854118 – 35854084 – 35853917 Fax: 35859858

Email: cmb@cmbegypt.com

www.cmb.eg

