

## Verona Polyurethane Matt Varnish 2:1

High-quality, matt wood polyurethane varnish 2:1 of two components.

### Specifications:

- Verona Polyurethane Matt Varnish 2:1 is a final, high-quality and matt clear varnish for wood, consisting of two components, based on polyurethane.

### Features:

- Strong adhesion, hardness and high residence to scratching and different weather condition.

### Uses:

- Used to paint all types of woodworks such as furniture and kitchens.

### How to use

- Prepare surfaces with suitable sealer, and sand it well.
- Mix Varnish with Hardener 200 by 2:1 directly before painting.
- Dilute Verona Polyurethane Matt Varnish 2:1 by adding 20 – 30 % using polyurethane thinner (Thinner S) to get the appropriate viscosity for use.
- Use a spray gun with a diameter of 1.4 – 1.6 mm.
- Spray within 4 – 5 hours after mixing the varnish with the hardener.

### Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 15 - 30 minutes.
- Hard Drying: 2 - 3 hours.
- Gloss at 60°: 10 – 25 - 45
- Consumption Rate: 9 - 11 m<sup>2</sup> / kg per film thickness of 40 microns.

### Safety Warnings:

- Avoid contact with skin and eyes.
- Wear a protective mask to avoid inhaling spray from painting.
- Close the container tightly after use.
- Keep out of the reach of the children.
- The product is flammable.

**Storage:** For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

**Packs:** A set of two components 1.35 kg, 6 kg, 6.75 kg.