

## Fast Varnish

High-gloss, fast-dry wood varnish.

### Specifications:

- Fast Varnish is a clear fast-dry and high-gloss manufactured from high-grade resins, and used to varnish all types of wood surfaces.
- Manufactured according to technical specification of CMB Company in accordance with the Ministerial Resolution No. 181 of 1996.

### Features:

- Fast dry, high gloss, clearness, strong adhesion.
- Ease of application and use.

### Uses:

- Used to paint all types of woodworks.

### How to use

- Clean surfaces well from dust, grease, oil or any other materials.
- Dilute Fast Varnish by adding 25 – 30 % of thinner or gasoline to get the desired viscosity for use.
- Paint one coat or more according to the surface need.
- **Application:** It can be painted with brush or roller.

### Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 10 - 15 minutes.
- Hard Drying: 30 – 60 minutes.
- Consumption Rate: 9 - 11 m<sup>2</sup> / kg.

### Safety Warnings:

- The product is flammable.
- Close the container tightly after use.
- Keep out of the reach of the children.

**Storage:** For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

**Packs:** 0.7 kg, 2.5 kg, 200 kg/baril.