

## Glossy Varnish

High-quality, glossy wood varnish, manufactured according to the Egyptian Standard Specifications No. 508/2006.

### Specifications:

- Glossy Varnish is a clear, high-quality varnish, based on advanced alkyd resins, and used to paint all types of wood surfaces.
- High gloss, clearness, strong adhesion, hardness and resistance to different weather conditions.
- Ease of application and use.

### Uses:

- Used internally to paint all types of woodworks such as furniture and kitchens.

### How to use

- Clean surfaces well from dust, grease, oil or any other materials.
- **For New Surfaces:** Paint the surface with a suitable sealer, then sand it after complete drying to get a smooth surface, and then finish it with two coats of Glossy Varnish.
- **For Old Surfaces:** Sand the surface well, and then finish it with two coats of Glossy Varnish.
- **Dilution:** Dilute Glossy Varnish by adding 10 – 15 % of mineral oil or turpentine to get the desired viscosity for use.
- **Application:** It can be painted with brush or roller.

### Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 3 - 4 hours.
- Hard Drying: 18 hours.
- Consumption Rate: 10 - 12 m<sup>2</sup> / kg per film thickness of 50 - 60 microns.

### Safety Warnings:

- The product is flammable.
- Close the container tightly after use.
- Keep out of the reach of the children.

**Storage:** For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

**Packs:** 0.7 kg, 3 kg, 200 kg/baril.