

## Marin varnish

High-quality glossy or matt varnish with alkyd polyurethane resin.

### Specifications:

- MARIN Varnish is a clear varnish of one component on alkyd polyurethane resin, used to varnish all types of woodworks and as a final coat for parquet and wood floors.

### Features:

- High gloss, clear, strong adhesion, hardness and resistance to different weather conditions.
- Ease of application and use, and resistance to abrasion.

### Uses:

- Used to paint all types of woodworks such as furniture, kitchens, boats and ships as well as to paint floors and parquet.

### How to use

- Clean surfaces well from dust, grease, oil or any other materials.
- **For New Surfaces:** Paint the surface with a suitable sealer, then sand it after complete drying to get a smooth surface, and then finish it with two coats of MARIN Varnish.
- **For Old Surfaces:** Sand the surface well, and then finish it with two coats of MARIN Varnish.
- **Dilution:** Dilute MARIN Varnish by adding 15 – 25 % of mineral oil or turpentine to get the desired viscosity for use.
- **Application:** It can be painted with brush or roller.

### Technical Characteristics: (at 25 ° C and humidity of 50%):

- Surface Drying: 1 – 2 hours.
- Time for Painting the Second Coat: 6 – 8 hours.
- Hard Drying: 16 hours.
- Consumption Rate: 10 - 12 m<sup>2</sup> / kg per film thickness of 50 - 60 microns.

### Safety Warnings:

- The product is flammable.
- Close the container tightly after use.
- Keep out of the reach of the children.

**Storage:** For two years from the date of production provided that the pack is kept closed and away from direct sunlight.

**Packs:** for Glossy 0.9 kg, 3 kg, 200 kg/baril.  
for Matt 0.8 kg, 3 kg, 200 kg/baril.