Wood Paints and Varnishes



Wood Serve

Protective varnish for wood.

Specifications:

- Brown, organic product to protect wood from rotting, cracking, moisture and insects.

Uses:

- Wood floors.
- Wood fences and ladders.
- Wood structures, exposed to moisture and dust.

ADVANTAGES:

- Poisonous to insects
- Permanent, i,e not liable to leach, to evaporate or to sublime.
- Non-corrosive to metals
- Capable of good penetration and does not increase the fire hazard.
- Distinctive but not unpleasant smell.

TECHNICAL DATA:

Technical Characteristics: (at 25 ° C):

- Color: Clear brown / black
- Hard Drying: 0.81 ± 0.01
- Initial Drying Time: 10 minutes.
- Final Drying Time: 30 minutes.
- Theoretical Consumption Rate: 12 m² / lt. per coat.

How to Use:

- Clean wood surfaces from dust and other contaminations.
- Apply with brush or roller.

Headquarters: 319 – 43 Al Haram St. – Giza Tel.: 35854118 – 35854084 – 35853917 Fax: 35859858

Email: cmb@cmbegypt.com www.cmb.eg



Safety Precautions:

- · Application should be carried out in well ventilated place.
- · Gloves, protective clothing and eye goggles should be worn during application.
- · Skin contaminations should be immediately cleaned with soap and plenty of water. Don't use solvent.
- If the material is splashed into the eyes, they should be immediately washed with water and then report to an eye specialist.
- · Do not eat or smoke during application.

Storage/shelflife:

For 5 years in suitable storing conditions.

Packages:

1 kg, 4 kg, 16 kg & 160 kg.

Headquarters: 319 – 43 Al Haram St. – Giza Tel.: 35854118 – 35854084 – 35853917 Fax: 35859858

Email: cmb@cmbegypt.com www.cmb.eg

خدمة العملاء Customer Service