

Floorbond

Multi Use Adhesive for Vinyl Tiles and Carpets.

Description:

- **FLOORBOND** is a ready-to-use high quality universal adhesive.
- Complies with CMBI TECH. SPCS. no. CMBI 2020.

Fields of Use:

- For bonding vinyl tiles, carpets and cork floor-covering to sub floors of wood, chip - board, concrete, ...etc.
- It is used also for bonding thick flooring materials to permeable and non-permeable surfaces.

Advantages:

- Is easily applied and has high spreadability, short aerating time, long working time and high bonding properties.

Technical Data : (at 25 °C)

Colour	brown
Density	1.2±0.02Kg/l
Aerating time	app.10 minutes
Working time	app.60 minutes
Initial drying time	24 hours
Final drying time	7 days
Application temperature	from +8°C to +25°C
Temperature resistance	about 60°C
Rate of use	800-1000 gm/m ²

Directions for Use:

- The substrate must be dry and free from dust, loose parts, oils, grease ... etc.
- Damaged or uneven floors should be repaired and levelled with an appropriate repair mortar.
- Apply a coat of **FLOORBOND** to the substrate with a toothed trowel.
- After 10 minutes, place the floor covering and press or roll firmly.
- Clean directly after use with water.

Safety Precautions:

- Wear gloves and goggles.
- Skin and face contamination should be washed with water and soap.
- Accidental splashes to eyes must be rinsed with clean water and then report to an specialist.
- Do not eat and smoke during use.

Storage:

- 12 months under suitable storage conditions.

Packages:

- 1 kg , 4kg and 15kg.