

## GLUTEKT

### Adhesive for Vinyl Flooring

#### DESCRIPTION :

- GLUTEKT : is based on bitumen, resins, organic solvents, special additives and fibrous materials .

#### FIELDS OF APPLICATION :

- Adhesive for all types of vinyl flooring .

#### ADVANTAGES :

- It can be easily applied on flooring by manual means .
- Retains its adhesive strength for a suitable period after application .
- Affords good adhesion between the substrate and vinyl flooring due to the presence of special additives that increase elasticity, adhesion and cohesion .
- It resists the penetration of water and therefore protects the flooring reinforcement from corrosion caused by the leakage of water .

#### TECHNICAL DATA :

Density ( at 25° C )	: 1.20 ± 0.10 kg/ L.
Surface dryness	: 60 minutes
Hard dryness	: 24 hours
Conforms to BS. 3941 - 1965, Type no (5)	

#### DIRECTIONS FOR USE :

- The flooring should be cleaned from dust and loose particles to ensure high adhesive strength .
- The contents of the can should be properly mixed before use .
- Apply a layer of GLUTEKT on the surface of flooring using a toothed trowel .
- After 10 - 15 minutes lay the vinyl flooring and press it firmly by means of a steel roller.
- After application of the GLUTEKT, all tools used should be cleaned with KEMSLOV 22 C .

#### RATE OF USE :

- 1 kg, covers 1 m<sup>2</sup>

#### STORAGE :

- 6 months under suitable storage conditions .

#### PACKAGE :

- 1 kg, 5 kg, 15 kg.