

Parquet-Bond

Parquet Flooring Adhesive.

Description:

- **PARQUET-BOND:** is an adhesive for parquet flooring, based on polyvinyl acetate.
- Complies with CMBI specification No.2040.

Fields of Use:

PARQUET-BOND: can be used to bond a variety of wooden parquet to concrete surfaces .

Advantages:

- Its special properties provide easy application, while ensuring that the beads of applied adhesive stand firmly without flowing, so as to permit maximum filling capacity and adhesion.

Technical Data : (at25 °C)

Colour	Beige
Dry solid content	approx. 69 %
Density	1.53 ± 0.02 kg/L
Viscosity	200 - 250 Poise
Max bond strength	24 hours
PH - value	8±0.5
Rate of use	800 - 1000 gm / m ²

Directions for Use:

- The floor should be even and flat ; holes should be filled first with mortar or repair filler. Old adhesive should be removed - highly porous floors should be pretreated with diluted adhesive 1 pt. to 7 pts. of water, 24 hours before laying the parquet.
- Both wood and floor should be dry and free from oil, grease and dust.
- Always stir the adhesive before using.
- The adhesive should be applied by notched spreader to prevent intrapped air.
- The wooden parquet should be pressed on the adhesive within 10 minutes of application.
- Clean tools directly after use with water.

Safety Precautions:

- Wear gloves and goggles.
- Skin and face contamination should be washed with water and soap.
- Accidental splashes to eyes must be rinsed with clean water and then report to an specialist.
- Do not eat and smoke during use.

Storage:

- 12 months under suitable storage conditions.

Packages:

- 1 kg, 5 kg and 20 kg.