

Construction Repair & Strengthening Products

KemSeal

Non Shrink Gypsum Product for Repairing Cracks in Plaster and Masonry Surfaces .

Description:

- **KEMSEAL** : is a non-shrink gypsum product for caulking and repairing of cracks and filling the pores of plaster and masonry surfaces.
- Complies with CMBI TECH. SPCS. no. 1100.
- packaging complies with ISO 6591 and ES 2254.

Fields of Use:

- Patching and caulking mortar for filling the cracks and smoothing the gypsum and cement plaster surfaces.

Advantages:

- Can be easily applied using a toothed trowel.
- Fast dry which saves the application time.

Technical Data : (at25 °C)

Colour	Off - white
Density (powder)	1.12 ± 0.02 kg/l
Density (Dry plaster)	1.35 ± 0.02 kg /l
Rate of use	1.35 kg / m ² / mm

Directions for Use:

- The surface should be free from oils, grease, weak and loose particles.
- Mix 2 parts of **KEMSEAL** with 1 part of water by volume.
- Dampen the very dry surfaces by means of a brush wetted with water.
- Hair cracks should be enlarged before **KEMSEAL** application.
- The surfaces can be smoothened after 2 hours from the application of **KEMSEAL** mortar.
- Apply **KEMSEAL** mortar for filling holes and fissures existing in walls, roofs and for flattening the surfaces by applying a layer of 5mm thick, and in the case of laying a greater thickness add to the mortar one third of its volume a graded clean sand (grain size 0-4 mm).

Safety Precautions:

- Wear gloves, overalls and goggles during handling & application.
- In case of contact, rinse off thoroughly with water.
- Wash hands with soap and water after use.

Storage:

- 6 months under dry and suitable storage conditions in closed sacks.

Packages:

- 5 kg, and 10 kg..