

CEROTEKT M2 (F)

Cold applied fiber reinforced bituminous protective coating.

Description :

- **CEROTEKT M2 (F)** is cold applied protective damp proofing or water proofing bituminous coating.
- **CEROTEKT M2 (F)** is a blend of selected bitumen, Fibers and solvents which dries to form a high quality bituminous film.
- Specifications : ASTM D 4479 (Type 1)

Fields of Use :

- Water proof coating and vapour barrier for all types of concrete, masonry and steel structures.
- Protective coating , for foundations and under ground structures.
- Anti - rust coating for steel structures.

Advantages :

- Cold applied , easy to use.
- Single component fiber reinforced.
- Excellent adhesion properties to most of building materials surfaces.
- High coverage rate.
- High resistance to aggressive salts in soil.
- Low cost compared with traditional hot applied bituminous materials.

Technical Data :(at 25° C)

- | | |
|-------------------------------|-------------------------------|
| • Water content (%) | 0 |
| • Density (kg/liter) | 0.90 ±0.05 |
| • Total bitumen content (%) | 60 – 70 |
| • Ash, max | 0.5 % |
| • Solvent | naphtha (5-10 %) if required |
| • Theoretical coverage | 2-3 m ² /kg/coat |

Directions For Use :

- The surfaces should be properly cleaned.
- Stir **CEROTEKT M2 (F)** before use. (add naphtha max 10 % if required).
- **CEROTEKT M2 (F)** can be applied using brushes, rollers or sprayers.
- The number of coats and the rate of use depends upon the purpose of use and the required thickness.

****Note:** for concrete surfaces apply primer coat with **CEROTEKT M2 (F)** diluted with 15 % naphtha .

Storage:

- 6 months under suitable storage conditions.

Packages:

- 1 kg & 3 kg & 15 kg & 120 kg drums.