

Cetox Fix

Fast Setting Mortar (5 Minute Set).

Description:

- **CETOX FIX** is a cementitious powder, chloride free, to be mixed only with water, Sets and hardens within few minutes.
- Complies with Egyptian code of practice for damp and water proofing.

Fields of Use:

- Fixing of bolts into concrete and masonry.
- Is used for quick waterproofing purposes under strong water leakage conditions.
- Sanitary and electrical installations.

Advantages:

- Reaches its high strength in few minutes and will be water tight.
- Chloride free so it does not cause rusting of steel.
- For interior and exterior applications.

Technical Data : (at 25° C)

Colour	Gray
Density (Powder)	1.5 ± 0.02 kg/l
(Dry mortar)	2.00 ± 0.02 kg/l
Mixing ratio by wt. (Cetox fix : water)	(3.7 ± 0.3) : 1
Working temperature	5°C to 25 °C
Full curing	15 minutes
Compressive strength ASTM C 109	265 ± 5% kg / cm ²
Rate of use	2 kg /l

Directions for Use:

- Base surface should be solid, firm, and free from dust, oil, grease and loose particles.
- Base surface must be prewetted.
- **CETOX FIX** is to be mixed only with water and possibly some sand max 1 : 1 by wt. but without any other binding material as cement, lime or gypsum.
- Mix only in small quantities which can be used within maximum 2 minutes.
- Setting starts just after 2 minutes of mixing and no additional water or further mixing is possible.
- Clean tools directly after work with water.

Safety Precautions:

- Wear gloves, overalls and goggles during handling & application.
- In case of contact, rinse off thoroughly with water.
- Wash hands with soap and water after use.

Storage / Shelf-Life:

- 12 months under dry and suitable storage conditions.

Packages:

- 1 kg, 5kg, 15 kg, and 25 kg.