

OXIDIZED CEROTECT M2

Cold applied, Fast dry bituminous protective coating.

Description:

- BLOWN CEROTECT M2 is cold applied protective damp proofing or water proofing bituminous coating.
- BLOWN CEROTECT M2 is a blend of blown bitumen and solvents which dries to form a high quality bituminous film.

Fields of Use:

- Water proof coating and vapour barrier for all concrete, masonry and steel structures.
- Protective coating, for foundations and under ground structures.
- Anti – rust coating for steel structures.

Advantages:

- Cold applied, easy to use.
- Single component.
- Excellent adhesion properties to most of building materials surfaces.
- Fast drying.
- High coverage rate.
- High resistance to aggressive salts and chemicals.
- Low cost compared with traditional hot applied bituminous materials.
- Resistant to weathering conditions..

Technical Data : (at 25 °C)

Water content (%)	0 %
Density	0.85 ± 0.05 (kg/L)
Total bitumen content	40 – 50 %
Initial dry	2 hours
Final dry	24 hours
Solvent	naphtha (5 – 10 %) if required
Theoretical Coverage	300 g/m ² for 150 micron thickness in case of concrete apply primer coat diluted with 15% naphtha.

Directions for Use:

- The surfaces should be properly cleaned.
- Stir **OXIDIZED CEROTECT M2** before use.(Add naphtha max 10% if required)
- **OXIDIZED CEROTECT M2** can be applied using brushes, rollers or sprayers.
- The number of coats and the rate of use depends upon the purpose of use and the required thickness.

**Not: for concrete surfaces apply primer coat diluted with 15% naphtha

Storage:

- 6 months under suitable storage conditions.

Packages:

- 1 kg , 4 kg , 15 kg and 160 kg drums.