

## Cetofill

Tile Joint Filler, White and grey

### Description:

- **CETOFILL** is cementitious compound modified with selected synthetic resins and chemical additives to ensure anti - fungal properties.
- Complies with CMBI TECH. SPCS. no. CMBI 1070.

### Fields of Use:

- Durable joint filler for glass, ceramic, mosaic vitreous tiles, synthetic and natural stones.
- Suitable for floor and wall covering tiles.

### Advantages:

- Ensures crack free setting up to 5.0 mm. joint width.
- Offers high water tightness and adhesion properties to all types of tiles.
- Can be coloured to suit all purposes.

### Technical Data :(at 25 °C)

Colour	White and grey ( other colours upon request)
Rate of use	4 - 6 m <sup>2</sup> of 15x15 cm tiles / kg Depends on dimensions of joints and tiles.

### Directions for Use:

- Prepare a paste of CETOFILL mixed with 25-30% clean water (1 kg. CETOFILL powder to 0.25 kg. water) by sprinkling the powder on the water and stirring to a pasty consistency free of lumps.
- The paste can be used immediately and within one hour after mixing.
- The paste is applied with a comb, first across and then combed out diagonally to the joint to ensure a complete filling of all joints.
- Immediately after drying begins, smooth down with a damp cloth or sponge and subsequently wipe the surface with dry cloth.
- At higher temperatures, the joint should be kept moist and protected from direct sunlight during setting time.

### Safety Precautions:

- 1- Wear gloves, overalls and goggles during handling & application.
- 2- In case of contact, rinse off thoroughly with water.
- 3- wash hands with soap and water after use.

### Storage / Shelf life:

- 12 months in dry and suitable storage conditions.

### Packages:

- 1 kg , 4 kg , 5 kg , 25 kg and 40 kg.

**CETOFILL for**  
**ceramic joint filling    Doors and windows    Swimming Pool**

