

Conflow BR

Floor Self-Levelling Compound.

Description:

- **CONFLOW BR** : is a cementitious powder compound modified with specially formulated synthetic resins, with graded quartz & bazalt from 1 - 4 mm. & special additives to increase bonding strength, workability and to prevent shrinkage.
- It forms after mixing with water a special mortar with high flexibility, free flowing, is quick drying and has self-levelling properties.
- Complies with CMBI TECH. SPCS. No. CMBI 1134.

Fields of Use:

- Is used for levelling of concrete and cement screed floors before laying vinyl coverings, carpets and parquet flooring.
- It can be also used for under-floor heating applications.

Advantages:

- Can be easily cast or pumped onto wet, dry concrete or cement screed surfaces.
- Ensures crack - free coverings from 10 - 50 mm. thickness.

Technical Data :(at 25° C)

Colour	Grey
Density (Mortar)	2.30 ± 0.05 kg/l
Pot life	30 minutes
Compressive strength (28 days)	450-550 kg/cm ² (acc. to water mixing ratio)
Rate of use	2.3 kg/m ² /mm

Directions for Use:

- The substrate must be sound, free of dust, dirt, oils, grease etc.
- Add the **CONFLOW BR** powder to the water gradually and stir thoroughly until a homogenous mix, free of lumps, is reached (Usually about 10 liter for each 100 kg of **CONFLOW BR**).
- According to the required thickness, the mortar is distributed on the substrate by using leveling plates.

Safety Precautions:

- Wear gloves, overalls and goggles during handling & application.
- In case of contact, rinse off thoroughly with water.
- Wash hands with soap and water after use.

Storage / Shelf life:

- 12 months in dry and suitable storage conditions .

Packages:

- 25 & 50 kg.